

## **C/CL-SERIE**

- 11 different models
- 100 mm Cam-lock panel system
- High attenuation by panel construction
- Pre-wired electrics, in wall ventilation and recessed lighting
- Isolated floating floor with vibration mounts
- High Performance Acoustic Door
- Range of options available
- CL-serie: low profile entrance
- Ideal for hospitals, clinics, hearing aid dispensers and training institutes
- Standard Colour: Linear White
- **Cam-lock system for easily dismantling and reassembly without loss of performance**

### **Dimensions in mm Single Wall cabin 100 mm**

Model/Type	Interior			Exterior			kg
	D	W	H	D	W	H	
<b>C-11</b>	1128	848	1981	1332	1052	2365	792
<b>C-12</b>	1412	1128	1981	1616	1332	2365	1029
<b>C-13</b>	1689	1412	1981	1893	1616	2365	1295
<b>C-14</b>	1969	1689	1981	2173	1893	2365	1573
<b>C-15</b>	2248	1969	1981	2452	2173	2365	1827
<b>C-16</b>	2530	2248	1981	2734	2452	2365	2087
<b>C-17</b>	2809	2530	1981	3013	2734	2365	2718

### **Double Wall cabin 100 mm**

<b>C-24</b>	1969	1690	1981	2573	2293	2569	3250
<b>C-25</b>	2249	1969	1981	2852	2573	2569	4017
<b>C-26</b>	2532	2249	1981	3134	2852	2569	4155
<b>C-27</b>	2811	2532	1981	3421	3134	2569	5114

### **Performance; dB Noise Reduction Single Wall**

Hz	125	250	500	1000	2000	4000	8000
	27	37	44	53	58	60	62

### **Performance; dB Noise Reduction Double Wall**

Hz	125	250	500	1000	2000	4000	8000
	44	59	75	86	91	>95	>95

